13 SEER PURON CONDENSING UNITS





13 SEER PURON CONDENSING UNITS



7.5 Bels

Washing

machine



The 538A/538B Condensing Unit is ideal for virtually every commercial application where space is limited or noise is an important consideration. The compact, quiet condenser features an advanced horizontal airflow design, low-velocity air discharge, energy-efficient operation, and low cost. Installation and maintenance are quick and easy.


Designed for use with the Bryant Duct-free Underceiling and Bryant fan and furnace coils. Provides high performance and reliability under the most demanding conditions.

Ultra-quiet operation

When sound ordinances and proximity to neighbors demand ultra-quiet operation, the 538A/538B is the right choice. The advanced, horizontal airflow design distributes air more evenly over the coil. The coil acts as an extra sound-suppressing device before the air is discharged at a very low velocity.

Takes up less yard space

This remarkably compact unit requires minimal service and airflow clearances, allowing it to be positioned as close as six inches (6") from an obstruction. The



condenser can be located virtually anywhere - on the ground, roof, balcony, under a deck, or mounted to an outside wall. When two units are required, they may even be stacked on top of each other.

13 SEER Puron

Additional features:

- 7.7 HSPF
- 200 ft. equivalent line length
- Multi-voltage & phase 036-060
- · Large accumulator
- · High-and Low-pressure safety switches
- Lock-out protection
- · Solid brass service valves
- · Galvanized steel casing with zinc phosphate coating
- · Scroll compressor for reliability and quietness
- · Available in heat pump Available accessories include:

6.8 Bels

538ANR

(Free Field Rating)

6.0 Bels

People

talking

- Low ambient controller (-20°F), field installed
- Winter-start
- · Wind baffle, stacking kit and wall mount kit

Cooling Only

Model A	Capacity	SEER	HSPF	Power	Phase	Sound Data	Outdoor Dimensions	Refrigerant Tubing	Mixed	Gas	Unit Weight
	Btu/Hr						(WxDxH in.)	Max Length	Phase		(lbs)
538ANR018000	18,000	13	n/a	208/230	1	68	36x15x25	200ft.	3/8"	5/8"	166
538ANR024000	24,000	13	n/a	208/230	1	66	36x15x32	200ft.	3/8"	5/8"	176
538ANR030000	30,000	13	n/a	208/230	1	72	45x17x38	200ft.	3/8"	3/4"	187
538ANR036000	36,000	13	n/a	208/230	1	72	45x17x38	200ft.	3/8"	3/4"	250
538APR036000	36,000	13	n/a	208/230	3	72	45x17x38	200ft.	3/8"	3/4"	250
538AER036000	36,000	13	n/a	460	3	72	45x17x38	200ft.	3/8"	3/4"	250
538ANR048000	48,000	13	n/a	208/230	1	72	45x17x43	200ft.	3/8"	7/8"	278
538APR048000	48,000	13	n/a	208/230	3	72	45x17x43	200ft.	3/8"	7/8"	278
538AER048000	48,000	13	n/a	460	3	72	45x17x43	200ft.	3/8"	7/8"	278
538ANR060000	60,000	13	n/a	208/230	1	72	45x17x43	200ft.	3/8"	7/8"	306
538APR060000	60,000	13	n/a	208/230	3	72	45x17x43	200ft.	3/8"	7/8"	306
538AER060000	60,000	13	n/a	460	3	72	45x17x43	200ft.	3/8"	7/8"	306

Heat Pump

M 11D	c	CEED	LICDE	D	DI.	C 1D (0 11 12 1	D. C	10. 1		TT 1. TIT 1 A .
Model B	Capacity	SEER	HSPF	Power	Phase	Sound Data	Outdoor Dimensions	Refrigerant Tubing	Mixed	Gas	Unit Weight
	Btu/Hr						(WxDxH in.)	Max Length	Phase		(lbs)
538BNR018000	18,000	13	7.7	208/230	1	68	36x15x25	200ft.	3/8"	5/8"	166
538BNR024000	24,000	13	7.7	208/230	1	66	36x15x32	200ft.	3/8"	5/8"	176
538BNR030000	30,000	13	7.7	208/230	1	72	45x17x38	200ft.	3/8"	3/4"	250
538BNR036000	36,000	13	7.7	208/230	1	72	45x17x38	200ft.	3/8"	3/4"	250
538BPR036000	36,000	13	7.7	208/230	3	72	45x17x38	200ft.	3/8"	3/4"	250
538BER036000	36,000	13	7.7	460	3	72	45x17x38	200ft.	3/8"	3/4"	250
538BNR048000	48,000	13	7.7	208/230	1	72	45x17x43	200ft.	3/8"	7/8"	278
538BPR048000	48000	13	7.7	208/230	3	72	45x17x43	200ft.	3/8"	7/8"	278
538BER048000	48,000	13	7.7	460	3	72	45x17x43	200ft.	3/8"	7/8"	278
538BNR060000	60,000	13	7.7	208/230	1	72	45x17x43	200ft.	3/8"	7/8"	306
538BPR060000	60,000	13	7.7	208/230	3	72	45x17x43	200ft.	3/8"	7/8"	306
538BFR060000	60 000	13	7 7	460	3	72	45v17v43	200ft	3/8"	7/8"	306





A member of the United Technologies Corporation family. Stock Symbol UTX.

© 2006 Bryant Heating & Cooling Systems, Syracuse, NY 02-538EN002-25

Due to Bryant's commitment to continuous improvement, specifications are subject to change without notice





