



COOLING ONLY

MODEL 538ANX/APX/AEX
CONDENSING UNIT



Visit the Energy Star website
at www.energystar.gov
for qualifying systems

Outdoor Solutions For Duct-Free Systems.

Bryant delivers quiet cooling, virtually anywhere.

The 538A Cool-only Condensing Unit is ideal for virtually every commercial application where space is limited or noise is an important consideration. The compact, quiet 538A features an advanced horizontal airflow design, low-velocity air discharge, energy-efficient operation, and low cost. Installation and maintenance are quick and easy, and the 538A is the only dedicated condensing unit with all safety features standard. This remarkably compact unit requires minimal service and airflow clearances, allowing it to be positioned as close as six inches (6") from an obstruction. Designed for use with Bryant Fan Coils. Provides high performance and reliability under the most demanding conditions.



Additional features:

- 12.0 SEER
- 200 ft. equivalent line length
- 150 ft. vertical lift
- Multi-voltage & phase 036-060
- Large accumulator
- High- and Low-pressure safety switches
- Lock-out protections
- Solid brass service valves

- Galvanized steel casing with zinc phosphate coating
- Scroll compressor for reliability and quietness
- Available in heat pump (538B)

Available accessories include:

- Low ambient controller (-20° F)
- Winter-start & Hard-start kits
- Wind baffle, stacking kit and wall mount kit



Money Isn't All You're Saving

Visit the Energy Star website at www.energystar.gov for qualifying systems

SPECIFICATIONS

MODEL	VOLTAGE	MCA	MOCP	VERT LIFT	VERT DROP	MAX TUBE LENGTH	TUBE CONNECTIONS	
							LIQUID	VAPOR
538ANX018000	208/230-1-60	10.7	15.0	65'	150'	200'	3/8" od	5/8" od
538ANX024000	208/230-1-60	16.8	25.0					3/4" od
538ANX030000	208/230-1-60	19.5	30.0					7/8" od
538ANX036000	208/230-1-60	23.2	40.0					
538APX036000	208/230-3-60	15.0	25.0					
538AEX036000	460-3-60	7.5	15.0					
538ANX048000	208/230-1-60	34.5	60.0					
538APX048000	208/230-3-60	20.2	35.0					
538AEX048000	460-3-60	11.1	15.0				1-1/8" od	
538ANX060000	208/230-1-60	36.6	60.0					
538APX060000	208/230-3-60	21.5	35.0					
538AEX060000	460-3-60	10.8	15.0					

MODEL	NOMINAL CAPACITY	SOUND RATING (dBa)		DIMENSIONS			WEIGHT
		POWER	PRESSURE	WIDTH	HEIGHT	DEPTH	
538ANX018000	18,000	66.1	57.8	36.9	25.1	14.6	150
538ANX024000	24,000	65.5	57.2				154
538ANX030000	30,000	63.0	54.7				169
538ANX036000	36,000	64.5	56.2				179
538APX036000							
538AEX036000							
538ANX048000	48,000	70.1	61.8	270			
538APX048000							
538AEX048000							
538ANX060000	60,000	69.4	61.1	290			
538APX060000							
538AEX060000							

Full expanded ratings available



www.bryant.com

Due to Bryant's commitment to continuous improvement, specifications are subject to change without notice.

© 2002 Bryant Heating & Cooling Systems, Syracuse, NY

Printed in U.S.A. 8538-011 (4/02)